

W773-W80

Intel® Xeon® W GPU Workstation



Features

- Intel® Xeon® W-3400 處理器
- Intel® W790 晶片
- 8-通道DDR5 RDIMM/3DS-RDIMM, 8 x DIMMs
- ASPEED® AST2600 BMC
- 雙通道10GbE 區域網路連接埠 (Intel® X710-AT2)
- 1 x 專用管理埠
- 最大支援 4個 x NVIDIA RTX™ A6000
- 5 x PCIe 第5代 x16 擴充插槽
- 2 x PCIe 第4代 x16 擴充插槽
- 2 x M.2 附 PCIe 第4代 x4 介面的插槽
- 多達8個3.5 吋/2.5 吋 SATA 硬碟托架
- 1個2000W ATX 80 PLUS Gold 電源

Specification

Dimensions	Pedestal (W726.3 x H218 x D455 mm)	Rear I/O	1 x VGA, 1 x COM, 2 x RJ45, 1 x MLAN, 3 x Audio jacks, 3 x USB 3.2 Gen2 Type-A, 1 x USB3.2 Gen2x2 Type-C, 1 x ID button with LED
Motherboard	MW83-RP0	TPM	1 x TPM header with SPI interface (optional TPM2.0 kit: CTM010)
CPU	Intel® Xeon® W-3400 Processors Single processor, TDP up to 350W	Power Supply	Single 2000W ATX 80 PLUS Bronze power supply AC Input: 100-240V
Socket	1 x LGA 4677	System Management	Aspeed® AST2600 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
Chipset	Intel® W790 Chipset	OS Compatibility	Windows 11 Enterprise (x64) Red Hat Enterprise Linux 9.0 (x64) Ubuntu 22.04 LTS (x64) CentOS Stream 9 (x64) Debian 11.5.0
Memory	8-Channel DDR5 memory, 8 x DIMM slots RDIMM modules up to 64GB supported RDIMM-3DS modules up to 256GB supported Memory speed: up to 4800 MHz	System Fans	Middle Fan: 3 x 120x120x38mm (4,400 rpm) Rear Fan: 1 x 120x120x25mm (2,800 rpm)
LAN	2 x 10 GbE LAN ports (Intel® X710-AT2) 1 x 10/100/1000 Management LAN (Realtek® RTL8211FD)	Operating Properties	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
Video	Integrated in Aspeed® AST2600: 1 x VGA Port	Packaging Content	1 x W773-W80, 1 x CPU Fan-sink 1 x Quick installation guide
Audio	Realtek® ALC897 HD audio codec Supports 2/4/5.1/7.1 channel configurations Rear 3 ports Audio Jack (Audio in/Audio out/Mic) Front 2 ports Audio Jack (Audio out/Mic)	Reference Numbers	Barebone package: 6NW773W80MR-00-1* - Motherboard: 9MW83RP0MR-00* - CPU Fan-Sink: 25ST0-0Z9221-A3R - Power supply: 25EP0-22000G-A0S - Rail Kit for W7x3 series ((A)+(B)+(C)): (A) 25AC0-W77301-K0R (Slide Rail), Q'ty: 1 set (B) 25HB4-HW77304-C0R (Rack Ear Right), Q'ty: 1 set (C) 25HB4-HW77305-C0R (Rack Ear Left), Q'ty: 1 set
Storage	4 x 3.5" / 2.5" SATA hot-swap HDD/SSD bays Additional 4 x 3.5" / 2.5" SATA hot-swap HDD/SSD bays (option)		
RAID	Intel® SATA RAID 0/1/10/5		
Expansion Slots	5 x PCIe x16 (Gen5 x16) slots 2 x PCIe x16 (Gen4 x16) slots 2 x M.2 slots: M-key, PCIe Gen4 x4, supports NGFF-2280 card		
Front I/O	2 x USB 3.2 Gen1 Type-A, 1 x Power Button, 1 x Reset Button, 1 x Audio/MIC Jack, 1 x Power LED, 1 x HDD LED, 1 x System LED		



Learn more about GIGABYTE server, visit <https://www.gigacomputing.com>

Engineered by



* All specifications are subject to change without notice. Please visit our website for the latest information.
* Intel, the Intel logo, Xeon, and other Intel marks are trademarks of Intel Corporation or its subsidiaries.
* All other brands, logos and names are property of their respective owners.

© 2023 Giga Computing Technology Co., Ltd. All rights reserved.